SAFETY DATA SHEET

Revision Date: 08/09/24

Section 1: Identification

PRODUCT AND COMPANY INFORMATION

Product Name: Poly(tert- butyl acrylate), solution in toluene

Catalog Number(s): 223 Molecular Formula: (C₇H₁₂O₂)_x

Company: Scientific Polymer Products, Inc.

6265 Dean Parkway Ontario, NY 14519

 Telephone:
 585/265-0413

 Fax:
 585/265-1390

 Website:
 www.scipoly.com

Emergency Phone Number: 800-255-3924 (CHEM TEL)

Section 2: Hazards Identification

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids, Category 2, H225 Skin irritation, Category 2, H315 Reproductive toxicity, Category 2, H361

Specific target organ toxicity- single exposure, Category 3, Central nervous system, H336

Specific target organ toxicity-repeated exposure, Category 2, H373

Aspiration hazard, Category 1, H304

GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260: Do not breathe dust/fumes/gas/mist/vapors/spray.

P264 Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313: IF exposed or concerned: Call a POISON CENTER or doctor/physician. Specific treatment (see supplemental first aid instructions on this label).

P331: Do NOT induce vomiting.

P332+P313: If skin irritation occurs: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse.

P370+P378: In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction.

P391: Collect spillage.

P403+P233: Store in a well ventilated place. Keep container tightly closed.

P403+P235: Store in a well ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/ container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) or not covered by GHS - none

To the best of our knowledge, the toxicological properties of this chemical have not been thoroughly investigated. Use appropriate procedures and precautions to prevent or minimize exposure.

Section 3: Composition/Information on Ingredients

Ingredient	CAS Number	Concentration (%)
Toluene	108-88-3	72 - 77%
Poly(tert-butyl acrylate)	25232-27-3	23 - 28%

Section 4: First Aid Measures

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eve contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

Section 5: Fire-Fighting Measures

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture

Carbon oxides

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13)

Reference to other sections

For disposal see section 13.

Section 7: Handling and Storage

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Use explosion proof equipment. Keep away from sources of ignition-No smoking. Take measure to prevent the buildup of electrostatic charge.

For precautions see section 2.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Specific end use(s)

Laboratory chemicals, Manufacture of substances

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

Component	CAS No.	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene	108-88-3	TWA: 20ppm	(Vacated)TWA: 100 ppm	IDLH: 500ppm
			(Vacated)TWA: 375mg/m3	TWA: 100ppm
			Ceiling: 300ppm	TWA: 375mg/m ³
			(Vacated)STEL: 150ppm	STEL: 150ppm
			(Vacated)STEL: 560mg/m ³	STEL: 560mg/m ³
			TWA: 200ppm	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Toluene	TWA: 50ppm TWA: 188mg/m³ Skin	TWA: 50ppm TWA: 188mg/m³	TWA: 20ppm

Legend:

ACGIH- American Conference of Governmental Industrial Hygienists

OSHA- Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air purifying respirators are appropriate use a full face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage of spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Section 9: Physical and Chemical Properties

No data available

No data available

Information on basic physical and chemical properties

a) b) c) d) e) f) g) h) i)	Appearance Odor Odor Threshold pH Melting point/freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability or explosive limits	Form: Liquid Sweet, pungent, Benzene like No data available No data available No data available 110 – 111°C (230 – 232°F) 4°C/ 39.2°F No data available No data available
3,	´Upper	6.70%
	Lower	1.40%
k)	Vapor pressure	No data available
I)	Vapor density	No data available
m)	Relative density	No data available

Partition coefficient: n- octanol/water

Water solubility

n) o) p) Auto-ignition temperature 535.0° C (995.0° F)
q) Decomposition temperature No data available
r) Viscosity No data available
s) Explosive properties No data available
t) Oxidizing properties No data available

Other safety information

No data available

Section 10: Stability and Reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapors may form an explosive mixture with air

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Other decomposition products- no data available

In the event of fire: see section 5

Section 11: Toxicological Information

Acute toxicity

Product information

Oral LD50 Dermal LD50 Vapor LC50 No acute toxicity information is available for this product

Based on ATE data, the classification criteria are not met. ATE>2000mg/kg Based on ATE data, the classification criteria are not met. ATE>2000mg/kg Based on ATE data, the classification criteria are not met. ATE>2000mg/kg

Component information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	>5000mg/kg (Rat)	12000mg/kg (Rabbit)	26700ppm (Rat) 1 h

Toxicologically synergistic

Products

No data available

Delayed and immediate effects as well as chronic effects from short and long term exposure

IrritationNo data availableSensitizationNo data available

Carcinogenicity The table below indicates whether each agency has listed any ingredient

as a carcinogen

Component	CAS No.	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed				
Poly(tert-butyl acrylate)	25232-27-3	Not listed				

Mutagenic effects No data available

Reproductive effectsNo data available

Developmental effectsNo data available

Teratogenicity No data available

STOT- single exposure Central Nervous System (CNS)

STOT- repeated exposure None known

Aspiration hazard No data available

Symptoms/effects, both acute and

Delayed

Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Endocrine disruptor information No data available

Other adverse effects The toxicological properties have not been fully investigated

Section 12: Ecological Information

Ecotoxicity

Do not empty into drains

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	12.5mg/L EC50 = 72h 433	50-70mg/L LC50 96 h	EC50 = 19.7mg/L 30 min	11.5mg/L EC50 = 48 h
	Mg/L EC50 > 96 h	5-7mg/L LC50 96 h		5.46
		15-19mg/L LC50 96 h		- 9.83mg/L EC50 48 h
		28mg/L LC50 96 h		
		12mg/L LC50 96 h		

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Section 13: Disposal Considerations

Waste treatment methods

Product

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional and national hazardous waste regulations to ensure complete and accurate classification.

Contaminated packaging

Dispose of as unused product.

Section 14: Transport Information

DOT (US)

UN number: 1294 Class: 3 Packing group: II

Proper shipping name: Toluene, solution

Reportable quantity (RQ): 167 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1294 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: TOLUENE, SOLUTION

IATA

UN number: 1294 Class: 3

Proper shipping name: Toluene, solution

Packing group: II

Section 15: Regulatory Information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS No.

Toluene 108-88-3

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right to Know Components

CAS No. Toluene 108-88-3

Pennsylvania Right to Know Components

CAS No.
Toluene 108-88-3
Poly(tert-butyl acrylate) 25232-27-3

New Jersey Right to Know Components

Toluene CAS No.
Tolytene 108-88-3
Poly(tert-butyl acrylate) 25232-27-3

California Prop. 65 Components

WARNING This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

other reproductive harm

CAS No. Toluene 108-88-3

Section 16: Other Information

HMIS Rating NFPA Rating

Health:2Health:2Flammability:3Flammability:3Reactivity:0Reactivity:0

This material is intended for laboratory use only. It is not sold or intended for drug, household or other uses. The information represents the most accurate and complete data currently available to us. However, we make no warranty, express or implied, with respect to such information, and we assume no liability resulting from its use.