

6265 DEAN PARKWAY ONTARIO NY 14519 WWW.SCIPOLY.COM

## **Technical Data Sheet**

**MATERIAL:** Poly(vinyl acetate)

CATALOG NUMBER: 347

**CAS NUMBER:** 9003-20-7

**DESCRIPTION:** Homopolymer of vinyl acetate

FORMULA:  $(C_4H_6O_2)_x$ 

**TYPICAL PROPERTIES:** 

Appearance: Beads

Approx Mw: 100,000 [GPC] Refractive index:  $n_D^{20}$  1.4665

Inherent viscosity: 0.42
Density: 1.18
Glass transition temp: 42°C
Softening point: 106°C

Solubility: Acetone, benzene, butyl acetate, carbon

tetrachloride, chloroform,

dichloroethylene, ethanol, ethyl acetate,

methanol, MIBK, THF, toluene

**GENERAL INFORMATION:** Polyvinyl acetate is a thermoplastic material which is useful in a wide

variety of coatings and adhesive applications. Some commercial applications include adhesives for packaging and labeling, in consumer adhesives such as white glues, in latex paints and in vinyl surface coatings. It is resistant to heat, light and to weak acid, alkaline and salt solutions and can be modified with plasticizers to control flexibility. Polyvinyl acetate is also used as a starting material for the preparation of

polyvinyl alcohol, polyvinyl butyral and polyvinyl formal.

**STRUCTURE:** 

Technical information and data regarding the composition, properties or use of the products described herein is believed reliable. However, no representation or warranty is made with respect thereto except as made by Sp<sup>2</sup> in writing at time of sale. Sp<sup>2</sup> cannot assume responsibility for any patent liability which may arise from the use of any product in a process, manner or formula not designed by Sp<sup>2</sup>.