

## **Technical Data Sheet**

MATERIAL:	Polybutadiene, phenyl terminated	
CATALOG NUMBER:	433	
CAS NUMBER:	9003-17-2	
DESCRIPTION:	Phenyl terminated polybutadiene homopolymer, 80% unsaturation	
FORMULA:	$(C_4H_6)_x$	
TYPICAL PROPERTIES:		
	Appearance:	Viscous liquid
	Approx Mn:	1,300
	Viscosity:	18 p (50°C)
	Density:	0.93 (20°C)
	Flash point:	> 500°F
	Solubility:	THF, toluene, xylene
	Microstructure (%)	-
	Vinyl 1,2:	45
	Trans 1,4:	20
	Cis 1,4:	15
	Saturated cyclic:	20
GENERAL INFORMATION:	Low molecular weight polybutadienes containing a high proportion of vinyl 1,2 unsaturation are peroxide curable and find application in ethylene-propylene rubber compositions used in electric cable manufacture and in thermoset moulding, potting and encapsulating compositions for electrical equipment. The cyclic components in the polybutadiana importate touchnase, thermal stability and supposition	
	polybutadiene imparts toughness, thermal stability and superior	

**STRUCTURE:** 

electrical properties to the cured polymers.

Technical information and data regarding the composition, properties or use of the products described herein is believed reliable. However, no representation or warranty is made with respect thereto except as made by Sp<sup>2</sup> in writing at time of sale. Sp<sup>2</sup> cannot assume responsibility for any patent liability which may arise from the use of any product in a process, manner or formula not designed by Sp<sup>2</sup>.