



## Technical Data Sheet

<b>MATERIAL:</b>	Poly[tetrafluoroethylene-co-perfluoro (alkyl vinyl ether)]	
<b>CATALOG NUMBER:</b>	637	
<b>CAS NUMBER:</b>	26655-00-5	
<b>DESCRIPTION:</b>	Copolymer of tetrafluoroethylene and perfluoro(propyl vinyl ether)	
<b>FORMULA:</b>	$(C_5F_{10}O \cdot C_2F_4)_x$	
<b>TYPICAL PROPERTIES:</b>	Appearance:	Pellets
	Density:	2.15
	Melt flow:	(260°C) 10.6 g./10 min
	Melting point:	305°C
	Solubility:	Insoluble in water
<b>GENERAL INFORMATION:</b>	Poly[tetrafluoroethylene-co-perfluoro(alkyl vinyl ether)] can be molded or extruded and has a chemical resistance equal to that of polytetrafluoroethylene. Its uses include lining pipe, valves and pumps.	
<b>STRUCTURE:</b>		

Technical information and data regarding the composition, properties or use of the products described herein is believed reliable. However, no representation or warranty is made with respect thereto except as made by Sp<sup>2</sup> in writing at time of sale. Sp<sup>2</sup> cannot assume responsibility for any patent liability which may arise from the use of any product in a process, manner or formula not designed by Sp<sup>2</sup>.