



Technical Data Sheet

MATERIAL:	Poly(vinyl methyl ether)														
CATALOG NUMBER:	899														
CAS NUMBER:	9003-09-2														
DESCRIPTION:	Homopolymer of vinyl methyl ether, 35% solids in water														
FORMULA:	$(C_3H_6O)_x$														
TYPICAL PROPERTIES:	<table><tr><td>Appearance:</td><td>Viscous liquid</td></tr><tr><td>Approx Mw:</td><td>200,000 [GPC]</td></tr><tr><td>Density:</td><td>1.05 (20°C)</td></tr><tr><td>Glass transition temp:</td><td>-34°C</td></tr><tr><td>Refractive index:</td><td>n_D^{25} 1.47</td></tr><tr><td>Boiling point:</td><td>100°C</td></tr><tr><td>Solubility:</td><td>Alcohols, aromatic and chlorinated hydrocarbons, esters, glycols, glycol esters, water</td></tr></table>	Appearance:	Viscous liquid	Approx Mw:	200,000 [GPC]	Density:	1.05 (20°C)	Glass transition temp:	-34°C	Refractive index:	n_D^{25} 1.47	Boiling point:	100°C	Solubility:	Alcohols, aromatic and chlorinated hydrocarbons, esters, glycols, glycol esters, water
Appearance:	Viscous liquid														
Approx Mw:	200,000 [GPC]														
Density:	1.05 (20°C)														
Glass transition temp:	-34°C														
Refractive index:	n_D^{25} 1.47														
Boiling point:	100°C														
Solubility:	Alcohols, aromatic and chlorinated hydrocarbons, esters, glycols, glycol esters, water														
GENERAL INFORMATION:	This polymer exhibits excellent adhesion to plastics, metals and coated surfaces. It is soluble in both water and organic solvents and finds applications in adhesives and coatings.														
STRUCTURE:															

Technical information and data regarding the composition, properties or use of the products described herein is believed reliable. However, no representation or warranty is made with respect thereto except as made by Sp² in writing at time of sale. Sp² cannot assume responsibility for any patent liability which may arise from the use of any product in a process, manner or formula not designed by Sp².