



Technical Data Sheet

MATERIAL:	Poly(ethylene oxide)	
CATALOG NUMBER:	136A	
CAS NUMBER:	25322-68-3	
DESCRIPTION:	Ethylene oxide homopolymer	
FORMULA:	$(C_2H_4O)_x$	
TYPICAL PROPERTIES:	Appearance:	Powder (98% thru 10 mesh)
	Approx Mw:	100,000
	Density:	1.21
	Glass transition temp:	-67°C
	Refractive index:	n_D^{20} 1.4539
	Viscosity (5% solution):	15 cp (5% solution @ 25°C)
	Melting point:	65°C
	Solubility:	Acetonitrile, benzene, chlorinated hydrocarbons, DMF, MEK, methanol, THF (hot), water

GENERAL INFORMATION: Poly(ethylene oxides) are soluble in an unusually broad range of solvents. Films of these resins are inherently flexible, tough and resistant to most oils and greases. They find use in a broad range of applications including adhesives, lubricant formulations, paint strippers, paper coatings, flocculants, binders, thickening agents, and water-soluble packaging.

STRUCTURE:

Technical information and data regarding the composition, properties or use of the products described herein is believed reliable. However, no representation or warranty is made with respect thereto except as made by Sp² in writing at time of sale. Sp² cannot assume responsibility for any patent liability which may arise from the use of any product in a process, manner or formula not designed by Sp².